Hindawi Publishing Corporation Advances in Materials Science and Engineering Volume 2013, Article ID 926540, 5 pages http://dx.doi.org/10.1155/2013/926540



Research Article

Microstructural Study of Neodmium Nickelate Doped with Strontium Synthesized by Gelatin Method

R. M. P. B. Oliveira,^{1,2} P. M. Pimentel,³ J. H. Araújo,⁴ D. M. A. Melo,¹ M. A. F. Melo,¹ and A. E. Martinelli¹

Correspondence should be addressed to R. M. P. B. Oliveira; rosaneboliveira@gmail.com

Received 14 December 2012; Revised 22 February 2013; Accepted 24 March 2013

Academic Editor: Steven Suib

Copyright © 2013 R. M. P. B. Oliveira et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

In this work nickelate nanoparticles were synthesized using a simple and fast new route, which makes use of gelatin as an organic precursor in order to evaluate the performance of the synthesis method to obtain materials and the influence of the strontium replacement on the structural parameters of the powders. Samples of $Nd_{2-x}Sr_xNiO_4$ (x=0 and 0.4) were calcined at 700 and 900°C at a heating of 10°C/min for 4 hours. X-ray powder diffraction patterns were obtained for all the samples, and the Rietveld Method was applied in order to determine the crystallite size using Scherrer's equation, the lattice parameters, and phase concentration. The results obtained using these techniques confirmed that the main crystal structure consists of the distorted K_2NiF_4 -type tetragonal I4/mmm. In addition, scanning electron microscopy images revealed the formation of nanosized particles.

1. Introduction

In recent years, the search for new perovskite-type oxides has been intensified due to the wide range of properties such as dielectric [1], catalytic activity [2] and electrocatalytic [3], optical [4], and magnetic properties [5]. The synthesis of these materials requires methods that provide a high surface area and high homogeneity. There are several methods for synthesis of perovskites, which directly affect the properties of these systems, specifically in its texture and specific surface area, oxidation states of cations, and oxygen stoichiometry. Traditional methods of preparation of perovskite-like materials adopted usually mixtures of constituents of oxides, hydroxides, or carbonates. However, as these materials generally have large particle size, these steps often require repeated and mixtures prolonged heating at high temperatures to produce a homogenous material and comprising a single phase. To overcome the disadvantages of low specific surface and limited control of the microstructure inherent in high

temperature processes, the precursors are generally obtained by processes such as sol-gel or coprecipitation of metal ions by precipitating agents such as hydroxides, cyanide, oxalate, and citrate ion, among others. Among the synthesis methods, the ceramic is the most widely used due to its simplicity but has the disadvantage of low specific area [6, 7].

Recently, a route has been developed for obtaining nanoscale materials using gelatin as the organic precursor that has the advantage of producing homogeneous and nanometric powders [8–10]. The procedure is the formation of colloidal dispersions between the gelatin and metal ions, which are connected gelatin coordinates groups such as NH₂ and COOH. The dispersion is subjected to heating to reduce volume and, consequently, formation of a gel which is subsequently calcined at a predetermined temperature for the decomposition of gelatin and formation of inorganic oxides. This study is focused on the preparation of solid solutions of neodymium nickelates doped with strontium by a method that makes use of gelatin as an organic precursor in order to

¹ Programa de Pós Graduação em Ciência e Engenharia de Materiais, Universidade Federal do Rio Grande do Norte, 59078-970 Natal, RN, Brazil

² Faculdade de Engenharia de Materiais, 68505-080 Marabá, PA, Brazil

³ Universidade Federal Rural do Semi-Árido, 59515-000 Angicos, RN, Brazil

⁴ Departamento de Física Teórica e Experimental, Universidade Federal do Rio Grande do Norte, 59078-970 Natal, RN, Brazil




FIGURE 1: The Rietveld refinement of the system $Nd_{2-x}Sr_xNiO_4$ to x = 0 calcined at (a) 700°C and (b) 900°C.

evaluate the structural properties of these oxides in function of increasing content of strontium and the heat treatment.

2. Experimental

Perovskites were prepared using gelatin as an organic precursor and metal nitrates as starting reagents. Gelatin was added to a beaker containing deionized water and stirred for 30 minutes at 50° C. Ni(NO₃)₂·6H₂O (99.9%, Sigma-Aldrich) and Nd(NO₃)₃·6H₂O (99.9%, Sigma-Aldrich) were added to the solution at 70° C for several minutes. Sr(NO₃) P.A. (\leq 99%, Sigma-Aldrich) was added for further 30 minutes. The temperature was slowly increased to 90° C, and the solution was stirred on a hot plate until a gel formed. The gel was then calcined at 350° C for 2 hours with a heating rate of 5° C min⁻¹. This resulted in a precursor powder, which was calcined at 700 and 900° C for 4 hours and characterized by X-ray diffraction (XRD) and scanning electron microscopy (SEM) techniques.

X-ray patterns were obtained from samples calcined at different Sr concentrations and temperatures. Measurements were recorded on a Shimadzu XRD-6000 diffractometer with polychromatic radiation of CuK α 1,2 (λ 1 = 1.5406 Å, λ 2 = 1.5445 Å). A 2 θ angular range was used between 10 and 90° with a scan speed of 2° min⁻¹ and step scan of 0.02°. Crystalline phases were identified using the International Center for Diffraction Data (ICDD) database. Crystallite sizes were obtained with Scherrer's equation. The Rietveld method was used to refine the XRD data using the MAUD program (version 2.044). The instrumental broadening has been used

following the procedure as adopted by Lutterotti and Scardi [11]. The analyses were carried out by observing the plot of calculated and observed patterns. The morphology of the ceramic powders $\mathrm{Nd}_{2-x}\mathrm{Sr}_x\mathrm{NiO}_4$ (x=0 and x=0.4) calcined at 700 and 900°C was observed by SEM images obtained in a scanning electron microscope model SSX-550 from Shimadzu.

3. Results and Discussions

Figure 1 shows the observed and calculated X-ray powder patterns of crystallization products of the $\mathrm{Nd}_{2-x}\mathrm{Sr}_x\mathrm{NiO}_4$ (x=0) powders calcined at 700°C and 900°C. According to a refinement, there is a good agreement between experimental and refined diffraction, indicating that the results are highly reproducible and reliable; that is, the model parameters of crystal structure ($low\ R\ Bragg$). The identified phases in the powder with x=0 were $\mathrm{Nd}_2\mathrm{O}_3$ hexagonal (JCPDS 41-1089), NiO cubic (JCPDS 73-1523), and NdNiO_3 rhombohedral. In samples calcined at 900°C appears to $\mathrm{Nd}_2\mathrm{NiO}_4$ orthorhombic (JCPDS 21-1274). According to Zhao et al. (1996) [12], oxides with $\mathrm{A}_2\mathrm{BO}_4$ structure ($\mathrm{K}_2\mathrm{NiF}_4$) are more stable then oxides with structure ABO $_3$ when is doped with strontium.

Figure 2 shows the Rietveld refinement data for $Nd_{2-x}Sr_xNiO_4$ (x=0.4) powder calcined at 700 and 900°C. The result shows a good agreement between experimental and refined XRD patterns. Table 1 shows the refined parameters for $Nd_{2-x}Sr_xNiO_4$ (x=0 and 0.4) powders calcined at 700 and 900°C, respectively. The inclusion of strontium in the structure on x=0.4 favors the formation of




Figure 2: The Rietveld refinement of the system Nd_{1.6}Sr_{0.4}NiO₄ calcined at 700 and 900°C.

Table 1: Refinement parameters of system $Nd_{2-x}Sr_xNiO_4$ to x=0 and x=0.4 calcined at 700°C and 900°C.

Sample	R Bragg	Phase	ICSD	Crystalline system	Space Group	Crystallite size (nm)	a (Å)	b Å	c Å
N.J. C. N.O	11.5	Nd_2O_3	32514	Trigonal	P-3m1	35.51	3.8302	3.8302	6.0046
$Nd_{2-x}Sr_xNiO_4$ $x = 0;700^{\circ}C$		NiO	9866	Cubic	Fm-3m	20	4.1791	4.1791	4.1791
		$NdNiO_3$	67722	Orthorhombic	Pbnm:cab	87.13	5.4311	5.4049	7.7910
$Nd_{2-x}Sr_xNiO_4$ $x = 0; 900^{\circ}C$	13.2	Nd_2O_3	32514	Trigonal	P-3m1	68.30	3.8301	3.8301	6.0036
		NiO	9866	Cubic	Fm-3m	42.94	4.1793	4.1793	4.1793
		$NdNiO_3$	67722	Orthorhombic	Pbnm:cab	43.78	5.5115	5.4280	7.6705
		Nd_2NiO_4	71137	Orthorhombic	Bmab	100	3.8054	12.3934	7.7910
$Nd_{2-x}Sr_xNiO_4$ $x = 0.4;700^{\circ}C$	12.07	$Nd_{1,6}Sr_{0,4}NiO_4$	71138	Tetragonal	I4/mmm	59.61	3.7831	3.7831	12.4603
		NiO	9866	Cubic	Fm-3m	23.91	4.1803	4.1803	4.1803
		Nd_2O_3	32514	Trigonal	P-3m1	100	3.8272	3.8272	5.9910
$Nd_{2-x}Sr_xNiO_4$ $x = 0.4;900^{\circ}C$	10.5	$Nd_{1,6}Sr_{0,4}NiO_4$	71138	Tetragonal	I4/mmm	110	3.7840	3.7840	12.4584
		NiO	9866	Cubic	P-3m1	64.79	4.1791	4.1791	4.1791

Table 2: Quantitative analysis of samples obtained by MAUD refinement.

Sample	Temperature (°C)	Phase (%)		
Nd C. NiO		Nd_2O_3	65	
$Nd_{2-x}Sr_xNiO_4$ $(x = 0)$	700	NiO	21	
		$NdNiO_3$	14	
		Nd_2O_3	58	
$Nd_{2-x}Sr_xNiO_4$	900	NiO	19.5	
(x = 0)		$NdNiO_3$	12	
		Nd ₂ O ₃ NiO NdNiO ₃ Nd ₂ O ₃ NiO	10.5	
$Nd_{2-r}Sr_rNiO_4$		$Nd_{1.6}Sr_{0.4}NiO_4$	77.5	
(x = 0.4)	700	NiO	20	
		Nd_2O_3	2.5	
$Nd_{2-x}Sr_xNiO_4$	900	$Nd_{1.6}Sr_{0.4}NiO_4\\$	80	
(x = 0.4)		NiO	20	

 $Nd_{2-x}Sr_xNiO_4$ tetragonal (JCPDS 80-2324) and NiO cubic (JCPDS 73-1523). For calcination at 900°C, Figure 2(b), for

x = 0.4, shows $\mathrm{Nd}_{2-x}\mathrm{Sr}_x\mathrm{NiO}_4$ tetragonal (JCPDS 80-2324) and NiO cubic (JCPDS 73-1523). It is known that the substitution in the perovskite-type oxide of a trivalent metal ion in the A site for a bivalent or tetravalent metal cation (A') is accompanied by a change in the oxidation state of the site B metal cation by modifying the activity catalyst. However, the change in oxidation state of the B site cation in the insertion of A' is accompanied by the formation of structural defects.

It is observed that the lattice parameter for the NdNiO $_3$ decreases due to oxidation of Ni $^{2+}$ to Ni $^{3+}$ compared with system Nd $_2$ NiO $_4$ when it is calcined at 900°C. It was reported that the substitution of Nd with Sr in Nd $_2$ NiO $_4$ might induce a structural phases transition from orthorhombic to tetragonal symmetry leading to a mixed valence (Ni $^{2+}$ /Ni 3) for the transition metal ion, which would in turn induce interesting electrical and magnetic properties in this system [13]. Moreover, increasing the lattice parameter c is due to replacement of ion Nd $^{3+}$ with Sr $^{2+}$ ion, promoting the removal of the layers in the structure of perovskite [14]. The quantitative phase analysis of samples obtained by MAUD program is given in Table 2.




FIGURE 3: (a) SEM image of system $Nd_{2-x}Sr_xNiO_4$ to x=0 calcined at $700^{\circ}C$; (b) $Nd_{1,6}Sr_{0,4}NiO_4$ calcined at $700^{\circ}C$; (c) $Nd_{2-x}Sr_xNiO_4$ to x=0 calcined at $900^{\circ}C$; (d) $Nd_{1,6}Sr_{0,4}NiO_4$ calcined at $900^{\circ}C$.

The morphology of the ceramic powders synthesized was determined by SEM images shown in Figure 3. By means of these images, it is observed that the particles have a rounded shape and uniform distribution of particle size. The particles are very small (less than 100 nm), and this is evident in all images corresponding to the $Nd_{2-x}Sr_xNiO_4$ (x=0 and x=0.4) powders calcined at 700 and $900^{\circ}C$.

The porous material has been generated during the evolution of gases formed from the decomposition of the gelatin during the calcination step. As shown in Figure 3(d), the quantity and pore size decrease with increasing temperature of calcination; this is a consequence of the phenomenon which leads to sintering of the agglomerated particles.

4. Conclusions

The synthesis route using gelatin was feasible for the synthesis of nanosized and porous ceramic powders, since it is a polymeric material containing groups which can coordinate with the metal ions as well as being a material of low cost and nontoxic.

The ceramic powders calcined under the conditions formed a solid solution whose main phase was perovskite-like for powders with partial replacement of Nd^{+2} metal ion with Sr^{+3} . In addition there were no significance differences

in the structures of these powders calcinated at $T = 700^{\circ}$ C and 900°C.


Acknowledgments

The authors are grateful to the Brazilian agencies Capes and CNPq for the financial support and GELITA for supplying the gelatin.

References

- C. P. L. Rubinger, R. L. Moreira, G. M. Ribeiro et al., "Intrinsic and extrinsic dielectric responses of CaCu₃Ti₄O₁₂ thin films," *Journal of Applied Physics*, vol. 110, no. 7, Article ID 074102, 2011.
- [2] R. Hu, R. Ding, J. Chen, J. Hu, and Y. Zhang, "Preparation and catalytic activities of the novel double perovskite-type oxide La₂CuNiO₆ for methane combustion," *Catalysis Communica*tions, vol. 21, pp. 38–41, 2012.
- [3] A. Galal, N. F. Atta, S. A. Darwish, A. A. Fatah, and S. M. Ali, "Electrocatalytic evolution of hydrogen on a novel SrPdO₃ perovskite electrode," *Journal of Power Sources*, vol. 195, no. 12, pp. 3806–3809, 2010.
- [4] D. T. M. Huong, N. H. Nam, L. V. Vu, and N. N. Long, "Preparation and optical characterization of Eu³⁺-doped CaTiO₃ perovskite powders," *Journal of Alloys and Compounds*, vol. 537, pp. 54–59, 2012.

- [5] J. Fan, B. Hong, L. Zhang et al., "Heisenberg-like ferromagnetism and percolative conductivity in the half-doped manganite Nd_{0.5}Ca_{0.25}Sr_{0.25}MnO₃," *Journal of Magnetism and Magnetic Materials*, vol. 322, no. 22, pp. 3692–3695, 2010.
- [6] F. Li, H. Zheng, D. Jia, X. Xin, and Z. Xue, "Syntheses of perovskite-type composite oxides nanocrystals by solid-state reactions," *Materials Letters*, vol. 53, no. 4-5, pp. 282–286, 2002.
- [7] C. Xiulan and L. Yuan, "New methods to prepare ultrafine particles of some perovskite-type oxides," *Chemical Engineering Journal*, vol. 78, no. 2-3, pp. 205–209, 2000.
- [8] N. A. S. Nogueira, E. B. da Silva, P. M. Jardim, and J. M. Sasaki, "Synthesis and characterization of NiAl₂O₄ nanoparticles obtained through gelatin," *Materials Letters*, vol. 61, no. 25, pp. 4743–4746, 2007.
- [9] A. S. de Menezes, C. M. R. Remédios, J. M. Sasaki et al., "Sintering of nanoparticles of α-Fe₂O₃ using gelatin," *Journal of Non-Crystalline Solids*, vol. 353, no. 11-12, pp. 1091–1094, 2007.
- [10] P. M. Pimentel, R. M. P. B. Oliveira, J. H. Araújo, F. S. Oliveira, O. R. Bagnato, and D. M. A. Melo, "Synthesis and structural characterization of Sm-Sr nickelates," *Journal of Chemistry and Chemical Engineering*, vol. 6, p. 526, 2012.
- [11] L. Lutterotti and P. Scardi, "Simultaneous structure and sizestrain refinement by the Rietveld method," *Journal of Applied Crystallography*, vol. 23, p. 246, 1990.
- [12] Z. Zhao, X. Yang, and Y. Wu, "Comparative study of Nickel-based perovskite-like mixed oxide catalysts for direct decomposition of NO," *Applied Catalysis B*, vol. 8, no. 3, pp. 281–297, 1996.
- [13] B. W. Arbuckle, K. V. Ramanujachary, Z. Zhang, and M. Greenblatt, "Investigations on the structural, electrical, and magnetic properties of $Nd_{2-x}Sr_xNiO_{4+\delta}$," *Journal of Solid State Chemistry*, vol. 88, no. 1, pp. 278–290, 1990.
- [14] M. Zaghrioui, F. Giovannelli, S. Pruvost, N. Poirot, and I. Monot-Laffez, "Magnetic and transport properties of Nd_{1.67}Sr_{0.33}NiO₄," *Journal of Magnetism and Magnetic Materials*, vol. 305, no. 1, pp. 71–75, 2006.





- ► Impact Factor **1.730**
- ▶ **28 Days** Fast Track Peer Review
- ▶ All Subject Areas of Science
- ▶ Submit at http://www.tswj.com